

CASC-OR ICE RACE CHAMPIONSHIP TECH & SAFETY CHECK LIST

| CAR# 2 nd CAR# □ | S | SC 🗆 l | RUBBE | ER . | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|---------------------|----------------|-------------|---------|
| SPECIFICATION | | RULE/RE | F ITE | M | Y IF OK |
| Roof mounted min 40mm stroke, 25cm high, black or white as well as fwd facing # max 7" high, black on white | n | 2.3 | NUN | MBERS | |
| ROOKIES must have rear facing triangle, min 5" | | 2.3.3 | | 1BERS | |
| orange on white board attached to back of # board | | | | | |
| NUMBERS MUST PASS BEFORE FURTHER SCRUTINEERING | | | | | T |
| Snell - 2005M & SA,2010M & SA, 2015M & SA | 1 | • | | TS | |
| Max. thick 52mm,hgt 204mm Front 460mm Rear. Must be bridged to fender. Truck bumpers 16" above ground. Fabricated bumpers not wider than the car and rounded or chamfered corners | 2. | .4 | BUMPE | ERS | |
| If fixed, windows to be open, net required | | | DOORS | | |
| Nets required if window open or removed | 2 | | | | |
| Same size left and right each axle. No trim. All lug | | 1.13 WINDOW WHEELS | | | |
| nuts | | 11./ | VVIILLL | _3 | |
| CASC/Subaru and any series sponsor decals on both sides | 5. | .8.8 | DECALS | | |
| Min. two 24W rear facing red brake light and one 55W rear facing amber running light – both clearly visible. All others to be removed | 2. | 2.1.12 | | S | |
| Required on passenger side if taking passengers | 2 | .1.8 (c) | GRAB H | ANDLE | |
| Bolted or welded securely to body | | 1.11 | BALLAST | | |
| Rubber/SSC - 3 point or 4 point | 2. | .8 | BELTS | | |
| Secure with head restraints | 2. | .1.8 (a) | SEATS | | |
| Must have fire walls. Must not leak if inverted | 2. | 1.9 | FUEL TANKS | | |
| Well Secured. Inside 'marine' box if located in interior. | 2. | .1.8 (d) | BATTE | ATTERY | |
| Brakes MUST function at each wheel. | 2. | 2.1.6 BRAKES | | S | |
| Exit behind driver. Secure at 2 points. Must be muffled. | 2. | 1.5 | EXHAUST | | |
| Must be on open, non-fixed roof | 2. | .7 | ROLL E | OLL BARS | |
| Must remain and be stock in appearance. Any material | 2. | 1.2 (d) | HOOD/ | OOD/FENDERS | |
| Pre 1972 must have side bars on both front doors | _ | 1.15 | - | OOR BEAMS | |
| Securely mounted. Scrutineer's discretion | 5. | 5.8.5 CAME | | RAS | |
| Airbags have been removed from the entire car | 2. | 1.22 | Body | | |
| Record method of disabling which will be used on this car. List in 'Y IF OK' space to right. | 5. | .8.3 | DISAB METHO | | |
| TECH INSP. SIGNATURE: | | | DATE: | | |