



**CANADIAN AUTOMOBILE SPORT CLUBS  
ONTARIO REGION**

**Appendix O, Section E - Formula 4**

**Effective April 19, 2020**

---

This page intentionally left blank

---



## Appendix O, Section E - Formula 4

© All material in this document is strictly the copyright of CASC Ontario Region and may not be reproduced without prior written permission.

These regulations are intended to assist in the conduct of Competitions and to further general safety. They are a guide and in no way guarantee against injury or death to participants, spectators or others. No express or implied warranties of safety or fitness for a particular purpose shall be intended or result from publication or compliance with these regulations. By applying for a competition licence and/or by entering a competition event, all participants are deemed to have understood and accepted these terms, including that motorsport is inherently dangerous and it is each participant's obligation to meet and maintain compliance with all regulations to reduce the risk of death or injury to self or others, recognizing that such risk is inherent to the sport and cannot be completely eliminated.

***Red bold, italics text indicates significant changes or amendments.***

### **CANADIAN AUTOMOBILE SPORT CLUBS ONTARIO REGION**

1110 Finch Avenue West  
Suite 222  
North York, ON  
M3J 2T2  
CANADA

Tel: (416) 667 9500  
Fax: (416) 667 9555  
Toll-Free In Canada: (877) 667-9505

office@casc.on.ca  
<http://casc.on.ca/>



---

# Contents

1	DEFINITION .....	5
2	EXCEPTIONS AND RESTRICTIONS.....	5
3	WEIGHT .....	5
4	ENGINE .....	5
5	FOOT PROTECTION .....	6



## APPENDIX O, SECTION E - FORMULA 4

### 1 DEFINITION

- 1.1.1 The Car shall be a single seat, four wheel, open-wheel racing Car.
- 1.1.2 Cars shall comply with the CASC-OR GCR and Race Regulations as well as the Regulations herein.

### 2 EXCEPTIONS AND RESTRICTIONS

- 2.1.1 An emergency brake is not required.
- 2.1.2 Fuel is allowed as stated under engine requirements.
- 2.1.3 A self-starter is not required.
- 2.1.4 Coachwork is defined as all external parts of the Car which are in the airstream and situated above a plane passing through the centre of the wheel hubs, with the exception of units definitely associated with the function of the engine, transmission, or the roll cage.
- 2.1.5 No part of the Car, except the safety rollover protection, shall exceed a height of 900mm (35.43in) from the roadway with the Driver normally seated. The roll cage shall not exert aerodynamic influence on the Car.
- 2.1.6 Behind the front wheels, no part of the coachwork shall extend beyond a vertical plane passing through the centreline of the wheels on either side of the Car with the wheels in the straight-ahead position.
- 2.1.7 The coachwork ahead of the front wheels may extend to the outer sides of the front tires with the wheels in the straight-ahead position.
- 2.1.8 Any coachwork which is in front of the front wheels and extends beyond the inner faces of the front tires shall not extend above the height of the front wheel rims.
- 2.1.9 Any specific part of the Car which has an aerodynamic influence on stability of the Car shall be mounted on an entirely sprung part of the Car and shall be firmly and immovably fixed while the Car is in motion.
- 2.1.10 All Cars running on other than pump fuel as available at a highway service station shall ensure there is an approved decal visible on the Car to denote the use of such fuel.
- 2.1.11 All Cars shall adhere to CASC-OR Regulations regarding catch tanks except:
  - a) Minimum capacity for 4-stroke cycle engine: 1 litre
  - b) 2-stroke cycle engines are exempt from crankcase overflow catch tank requirements.

### 3 WEIGHT

The weight of the Car including coolant, lubricants, fuel, and Driver with the safety equipment specified in Appendix I - Driver Safety Equipment shall be not less than 374.22 kg. (825 lbs.). Cars with engines specified in 4.1.1.f below shall be exempt from this rule.

### 4 ENGINE

- 4.1.1 The engine shall be based on a production engine of which more than 1000 of the model have been produced, and shall conform to the following;
  - a) It shall not exceed the manufacturer's first over-bore giving a displacement greater than the stated maximum.

- b) It shall have a maximum displacement of 750cc. (2 or 4 stroke cycle), with the exception of 4.1.1 f below.
- c) It shall be normally aspirated, and be burning commercially available gasoline, alcohol, or alcohol/gasoline mix.
- d) Cars using alcohol shall display the appropriate decals per 2.1.10 above.
- e) All 2-cycle engines shall be equipped with a muffling device on each exhaust pipe.
- f) Any four-stroke cycle engine having 2 valves per cylinder and any piston ported two-stroke cycle engine may have a maximum displacement of 850 cc.

## **5 FOOT PROTECTION**

All Cars shall have a main frame, or suitable extension, which encloses the foot pedals at their foremost depression.