



CASC-OR ICE RACE CHAMPIONSHIP

TECH & SAFETY CHECK LIST

CAR# _____ 2 nd CAR# _____ <input type="checkbox"/> SSC <input type="checkbox"/> RUBBER			
SPECIFICATION	RULE/REF	ITEM	Y IF OK
Roof mounted min 40mm stroke, 25cm high, black on white as well as fwd facing # max 7" high, black on white	2.3	NUMBERS	
ROOKIES must have rear facing triangle, min 5" orange on white board attached to back of # board	2.3.3	NUMBERS	
NUMBERS MUST PASS BEFORE FURTHER SCRUTINEERING			
Snell – 2005M & SA, 2010M & SA, 2015M & SA	3.0	HELMETS	
Max. thick 52mm, hgt 204mm Front 460mm Rear. Must be bridged to fender. Truck bumpers 16" above ground. <i>Fabricated bumpers not wider than the car and rounded or chamfered corners</i>	2.4	BUMPERS	
If fixed, windows to be open, net required		DOORS	
Nets required if window open or removed	2.1.13	WINDOWS	
Same size left and right each axle. No trim. All lug nuts	2.1.7	WHEELS	
CASC/Subaru and any series sponsor decals on both sides	5.8.8	DECALS	
Min. two 24W rear facing red brake light and one 55W rear facing amber or white running light – both clearly visible. All others to be removed	2.1.12	LIGHTS	
Required on passenger side if taking passengers	2.1.8 (c)	GRAB HANDLE	
Bolted or welded securely to body	2.1.11	BALLAST	
Rubber/SSC – 3 point or 4 point	2.8	BELTS	
Secure with head restraints	2.1.8 (a)	SEATS	
Must have fire walls. Must not leak if inverted	2.1.9	FUEL TANKS	
Well Secured. Inside 'marine' box if located in interior.	2.1.8 (d)	BATTERY	
Brakes <i>MUST</i> function at each wheel.	2.1.6	BRAKES	
Exit behind driver. Secure at 2 points. Must be muffled.	2.1.5	EXHAUST	
Must be on open, non-fixed roof	2.7	ROLL BARS	
Must remain and be stock in appearance. Any material	2.1.2 (d)	HOOD/FENDERS	
Pre 1972 must have side bars on both front doors	2.1.15	DOOR BEAMS	
Securely mounted. Scrutineer's discretion	5.8.5	CAMERAS	
Airbags have been removed from the entire car	2.1.22	Body	
Record method of disabling which will be used on this car. List in 'Y IF OK' space to right.	5.8.3	DISABLING METHOD	
TECH INSP. SIGNATURE:			DATE: